

Model	Load Capacity	Maximum Beam	Lift Height	Lift Mechanism	Adjustable Legs	Platform Length	Overall Width (w/base pads)	Shipping Weight	Stainless Steel Hardware	Motor Stop	Ultrabunks
SSV1288	1200	88	3'6"	B1500 Winch	2 @ 20	8'	8'3"	220			
SSV1288-4	1200	88	3'6"	B1500 Winch	4 @ 20	8'	8'3"	281		✓	✓
SSV15100	1500	100	4'	129:1 Lift Ratio	4 @ 20	9'2"	9'8"	375		✓	✓
SSV20100	2000	100	4'	193:1 Lift Ratio	4 @ 20	9'2"	9'8"	385		✓	✓
SSV30108	3000	108	4'	258:1 Lift Ratio	4 @ 20	9'2"	10'4"	450		✓	✓
SSV30120	3000	120	4'	258:1 Lift Ratio	4 @ 20	9'2"	11'4"	470		✓	✓
SSV40108	4000	108	4'	386:1 Lift Ratio	4 @ 20	9'2"	10'4"	460		✓	✓
SSV40120	4000	120	4'	386:1 Lift Ratio	4 @ 20	9'2"	11'4"	480		✓	✓
SSV60108	6000	108	4'6"	460:1 Lift Ratio	4 @ 20	11'2"	10'4"	850		✓	✓
SSV60120	6000	120	4'6"	460:1 Lift Ratio	4 @ 20	11'2"	11'4"	850		✓	✓
SSV15100 DW	1500	100	4'	129:1 Lift Ratio	4 @ 55	9'2"	9'8"	400		✓	✓
SSV20100 DW	2000	100	4'	193:1 Lift Ratio	4 @ 55	9'2"	9'8"	410		✓	✓
SSV30108 DW	3000	108	4'	258:1 Lift Ratio	4 @ 55	9'2"	10'4"	475		✓	✓
SSV30120 DW	3000	120	4'	258:1 Lift Ratio	4 @ 55	9'2"	11'4"	495		✓	✓
SSV40108 DW	4000	108	4'	386:1 Lift Ratio	4 @ 55	9'2"	10'4"	485		✓	✓
SSV40120 DW	4000	120	4'	386:1 Lift Ratio	4 @ 55	9'2"	11'4"	505		✓	✓
SSV60120 DW	6000	120	4'6"	460:1 Lift Ratio	4 @ 52.5	11'2"	11'4"	895		✓	✓
SSPV30108	3000	108	4'	258:1 Lift Ratio	4 @ 20	9'2"	10'4"	450			
SSPV30120	3000	120	4'	258:1 Lift Ratio	4 @ 20	9'2"	11'4"	470			
SSPV40108	4000	108	4'	386:1 Lift Ratio	4 @ 20	9'2"	10'4"	460			
SSPV40120	4000	120	4'	386:1 Lift Ratio	4 @ 20	9'2"	11'4"	480			
SSV15100SS	1500	100	4'	129:1 Lift Ratio	4 @ 20	9'2"	9'8"	375	✓	✓	✓
SSV20100SS	2000	100	4'	193:1 Lift Ratio	4 @ 20	9'2"	9'8"	385	✓	✓	✓
SSV30108SS	3000	108	4'	258:1 Lift Ratio	4 @ 20	9'2"	10'4"	450	✓	✓	✓
SSV30120SS	3000	120	4'	258:1 Lift Ratio	4 @ 20	9'2"	11'4"	470	✓	✓	✓
SSV40108SS	4000	108	4'	386:1 Lift Ratio	4 @ 20	9'2"	10'4"	460	✓	✓	✓
SSV40120SS	4000	120	4'	386:1 Lift Ratio	4 @ 20	9'2"	11'4"	480	✓	✓	✓
SSPV30108SS	3000	108	4'	258:1 Lift Ratio	4 @ 20	9'2"	10'4"	450	✓		✓
SSPV30120SS	3000	120	4'	258:1 Lift Ratio	4 @ 20	9'2"	11'4"	470	✓		✓
SSPV40108SS	4000	108	4'	386:1 Lift Ratio	4 @ 20	9'2"	10'4"	460	✓		✓
SSPV40120SS	4000	120	4'	386:1 Lift Ratio	4 @ 20	9'2"	11'4"	480	✓		✓
SS36110 (Steel)	3600	110	4'	200:1 Winch	4 @ 18	9'6"	10'6"	1045			
SSV45120 (Steel)	4500	120	4'	386:1 Winch	4 @ 36	11'	11'3"	1200			



Tiger Docks
Waterfront Specialists

For sales in your area contact:
www.tigerdocks.com
636.272.4300