

Sunstream **Small Craft Lifts**

DockJock Models **DJ1000A4** **DJ1000A6** **DJ1000D4** **DJ1000D6**

| Power Source | A/C power | A/C power | D/C power | D/C power |
|--------------------------|-----------|-----------|-----------|-----------|
| Capacity (pounds) | 1,000 | 1,000 | 1,000 | 1,000 |
| Lifting Range | 48" | 84" | 48" | 84" |
| Track Length | 72" | 96" | 72" | 96" |
| Arm Width | 40" | 40" | 40" | 40" |
| Optional Extended Length | 60" | 60" | 60" | 60" |
| Weight (pounds) | 121 | 134 | 121 | 134 |

SunLift Mini

SL2006AR

SL2008AR

| | | |
|--|-------------|-------------|
| Capacity (pounds) | 2,000 | 2,000 |
| Lifting Ranges* | 36"/48"/60" | 36"/48"/60" |
| Capacity at 48" & 60" Lifting Range (pounds) | 1,800 | 1,800 |
| Bunk Length | 6' | 8' |
| Frame Length | 95" | 95" |
| Frame Width | 5'6" | 5'6" |
| Weight (pounds) | 200 | 210 |
| Lifting Speed (Typ.) | 15 sec | 15 sec |
| Min. Water Depth Required (Typ.) | 18" | 18" |
| Remote Control | Opt. | Opt. |

*Some lifting ranges require optional leg extensions. Standard range is 36".



For sales in your
area contact:

Tiger Docks
Waterfront Specialists

www.tigerdocks.com
636.272.4300

Specifications can vary due to several factors.