

# Specifications



For sales in your  
area contact:  
**Tiger Docks**  
Waterfront Specialists  
www.tigerdocks.com  
636.272.4300

## Sunstream SunLift™

SunLift Model	SL2006AR	SL2008AR	SL3010	SL4010AR	SL6012AR	SL8012ER	SL10014ER	SL12018ER	SL18020ER	SL24022ER
Capacity (pounds)	2,000	2,000	3,000	4,000	6,000	8,000	10,000	12,000	18,000	24,000
Lifting Ranges*	36"/48"/60"	36"/48"/60"	48"	36"/48"/60"/(72"**)	36"/48"/60"/(72"**)	60"/(72"**)	60"/(72"**)	60"/(72"**)	60"/(72"**)	60"/(72"**)
Capacity at Max. Lifting Range	1,800	1,800	3,000	4,000	4,500	8,000	9,500	9,500	14,250	19,000
Bunk Length	6'	8'	10'	10'	12'	12'	14'	18'	20'	22'
Frame Length	95"	95"	10'5"	10'5"	12'5"	12'5"	14'5"	18'5"	20'5"	24'
Frame Width	5'6"	5'6"	9'6"	9'6"	10'	11'	11'	11'	12'6"	12'6"
Weight (pounds)	200	210	450	550	655	1,000	1,050	1,500	2,000	2,500
Lifting Speed (Typ.)	15 sec	15 sec	15 sec	25 sec	35 sec	50 sec	50 sec	50 sec	55 sec	60 sec
Min. Water Depth Required (Typ.)	18"	18"	23"	25"	27"	36"	40"	44"	50"	62"
Min. Depth w/Shallow Water Roller (Typ.)	N/A	N/A	N/A	16"	17"	30"	34"	38"	N/A	N/A
Remote Control	Opt.	Opt.	Opt.	Std.	Std.	Std.	Std.	Std.	Std.	Std.
Leg Lengths Available	2'-12"	2'-12"	2'-16"	2'-16"	2'-16"	2'-16"	2'-16"	2'-16"	2'-16"	2'-16"

\*Some lifting ranges require optional leg extensions. Standard ranges are shown with underline (example: 36").

\*\* Special Order Model XR 72" Range.